

POWERFUL PRODUCTS

FLEXICON

FLEXIBLE CONDUIT & ACCESSORIES

Flexible Nylon Conduit Contractor Packs

Packs contain:

- 10m Black Nylon Conduit
- 10 x IP66 Straight Fittings
- 5 x DNA Isolators

- Extremely flexible Nylon conduit
- Highly UV resistant
- Snap-on IP66 fittings
- Easy screwdriver removal
- Oil & solvent resistant
- Extra low fire hazard
- Great temperature range -40°C to +120°C
- High impact strength - crush resistant
- Abrasion resistant

PACK 1 \$102.60 +GST

20mm Nylon corro pack
Includes 10m hose, 10 x straight fitting & locknuts, 5 x 1p 32A isolators
Use part no - FPAS-CP20 1P 32A

PACK 2 \$121.60 +GST

25mm Nylon corro pack
Includes 10m hose, 10 x straight fitting & locknuts, 5 x 1p 32A isolators
Use part no - FPAS-CP25 1P 32A

PACK 3 \$122.60 +GST

20mm Nylon corro pack
Includes 10m hose, 10 x straight fitting & locknuts, 5 x 3p 63A isolators
Use part no - FPAS-CP20 3P 63A

PACK 4 \$141.60 +GST

25mm Nylon corro pack
Includes 10m hose, 10 x straight fitting & locknuts, 5 x 3p 63A isolators
Use part no - FPAS-CP25 3P 63A



Special finishes end May 2010 or at the discretion of N.A.W. Controls

98 Commercial Drive, Thomastown Victoria 3074

Telephone: (03) 9464 6555 Fax: (03) 9464 5155

Email: sales@nawcontrols.com.au

Web: www.nawcontrols.com.au

Other styles available:

- STAINLESS STEEL 316 (TYPE SSU)
- GALVANISED STEEL, ZINC (TYPE FU)

GALVANISED STEEL PVC COATED (TYPE FSU)

Construction

Galvanised steel , helically wound, flexible steel conduit with PVC coating.
Colour black or orange

Features:

- High mechanical strength
- Highly flexible
- Temperature range - -15 deg C to +70 deg C
- IP rating - IP 54 with standard fittings, IP 65 with type C compression fittings (please enquire)

Conduits

Part no.	Outside diam. (mm)	Inside diam. (mm)	Minimum inside bend radius (mm)	Reel lengths (m)	Price \$ per metre
FSU16B	17	13	40	10, 25, 50	7.86
FSU20B	21.5	16.9	45	10, 25, 50	8.61
FSU25B	26	21.1	55	10, 25, 50	11.74
FSU32B	34	28.1	70	10, 25	18.73

Fittings

Part no.	Metric Thread (mm)	Pack qty	Price ea \$	Part no.	Metric Thread (mm)	Pack qty	Price ea \$
FSU16-M16-M	16	10	5.48	FSU20-M20-S	20	10	7.77
FSU16-M16-S	16	10	7.64	FSU25-M25-M	25	10	9.09
FSU16-M20-M	20	10	5.50	FSU25-M25-S	25	10	11.84
FSU16-M20-S	20	10	7.71	FSU32-M32-M	32	2	12.58
FSU20-M20-M	20	10	5.50	FSU32-M32-S	32	2	16.23



FSU20-M20-M



FSU20B

GALVANISED STEEL BRAIDED (TYPE FSB)

Construction

Galvanised steel, helically wound with PVC coating and galvanised steel overbraided. Colour Zinc

Features


- High mechanical strength
- Highly flexible
- IP rating - IP54
- High abrasion resistance
- Temperature range - -15 deg C to +70 deg C

Conduits

Part no.	Outside diam. (mm)	Inside diam. (mm)	Minimum inside bend radius (mm)	Reel lengths (m)	Price \$ per metre
FSB16	18.2	13	40	25	18.85
FSB20	22.7	16.9	45	25	24.37
FSB25	27.2	21.1	55	25	26.77

Fittings

Part no.	Metric Thread (mm)	Pack qty	Price ea \$	Part no.	Metric Thread (mm)	Pack qty	Price ea \$
FSB16-M16-M	16	10	11.48	FSB20-M20-M	20	10	11.70
FSB16-M16-S	16	10	15.54	FSB20-M20-S	20	10	15.75
FSB16-M20-M	20	10	11.59	FSB25-M25-M	25	10	14.72
FSB16-M20-S	20	10	15.69	FSB25-M25-S	25	10	20.06



FSB20-M20-S



FSB20

Flexible Conduits



- SMOOTH SPIRAL REINFORCED PVC (TYPE LPC)
- RANGE OF ACCESSORIES

GALVANISED STEEL PVC COATED LIQUID TIGHT (TYPE LTP)

Construction

Galvanised steel , helically wound, flexible conduit with smooth PVC cover.
Colour black, grey and orange

Features


- High mechanical strength • Good flexibility • IP rating - IP 68
- Smooth wipe clean outer cover • Temperature range - -20 deg C to +105 deg C

Conduits

Part no.	Outside diam. (mm)	Inside diam. (mm)	Minimum inside bend radius (mm)	Reel lengths (m)	Price \$ per metre
LTP16	17.8	12.6	45.00	10, 25, 50	10.47
LTP20	21.1	16	65.00	10, 25, 50	11.42
LTP25	26.4	21	100.00	10, 25, 50	15.18
LTP32	33.1	26.5	135.00	10, 25	23.54

Fittings

Part no.	Metric Thread (mm)	Pack qty	Price ea \$	Part no.	Metric Thread (mm)	Pack qty	Price ea \$
LTP16-M16-C	16	10	8.12	LTP20-M20-C90	20	10	12.94
LTP16-M16-C90	16	10	12.36	LTP25-M25-C	25	10	12.27
LTP16-M20-C	20	10	8.20	LTP25-M25-C90	25	10	19.25
LTP16-M20-C90	20	10	12.82	LTP32-M32-C	32	2	13.66
LTP20-M20-C	20	10	8.27	LTP32-M32-C90	32	2	24.31



LTP20-M20-C



LTP20

CORRUGATED NYLON (TYPE FPAS)

Construction

Standard weight, flame retardant, Nylon (PA6) Corrugated flexible conduit. Colour - black

Features

- Highly flexible and high fatigue life • High impact strength and recovers if crushed
- IP rating - IP66. IP68 available. • Lloyds register type approval
- Temperature range - -40 deg C to +120 deg C (-20 deg c to +100 deg C for moving applications)
- Low fire hazard • UL 94 V2 • Halogen, sulphur and phosphorous free

Conduits

Part no.	Outside diam. (mm)	Inside diam. (mm)	Minimum inside bend radius (mm)	Reel lengths (m)	Price \$ per metre
FPAS16	15.8	11.8	40	25, 50	5.10
FPAS21	21.2	16.7	45	25, 50	6.91
FPAS28	28.5	22.8	50	25, 50	10.33
FPAS34	34.5	28.1	60	25, 50	15.96

Fittings

Part no.	Metric Thread (mm)	Pack qty	Price ea \$	Part no.	Metric Thread (mm)	Pack qty	Price ea \$
FPA16-M16	16	10	2.93	FPA21-M20-90	20	10	5.84
FPA16-M16-90	16	10	4.38	FPA28-M25	25	10	5.30
FPA16-M20	20	10	2.93	FPA28-M25-90	25	10	9.21
FPA16-M20-90	20	10	4.79	FPA34-M32	32	10	7.10
FPA21-M20	20	10	3.34	FPA34-M32-90	32	10	11.60



FPA21-M20-90



FPAS21

FLEXICON®

FLEXIBLE CONDUIT & ACCESSORIES

* All prices shown are trade prices and are exclusive of GST

IP65 METAL ENCLOSURE - RAL 7032

Polyester powder coated RAL 7035, Concealed hinges give 130 deg opening
Earthing on door, body and mounting plates, Wall mounting brackets available
Internal doors also available, Complete with mounting plate

Part No.	Height	Width	Depth	Gland Opening	Locks	Price \$
EUR252010	250	200	100	0	1	135.35
EUR252015	250	200	150	0	1	147.60
EUR302515	300	250	150	1	1	204.40
EUR302520	300	250	200	1	1	216.55
EUR303015	300	300	150	1	1	225.30
EUR303020	300	300	200	1	1	235.50
EUR403015	400	300	150	1	1	243.60
EUR403020	400	300	200	1	1	282.85
EUR404020	400	400	200	1	1	291.00
EUR504015	500	400	150	1	1	385.75
EUR504020	500	400	200	1	1	416.85
EUR504025	500	400	250	1	1	431.75
EUR505020	500	500	200	1	1	431.75
EUR505025	500	500	250	1	1	439.90
EUR604015	600	400	150	2	2	433.10
EUR604020	600	400	200	2	2	448.00
EUR604025	600	400	250	2	2	456.45
EUR605020	600	500	200	2	2	473.70
EUR605025	600	500	250	2	2	494.00
EUR606020	600	600	200	2	2	518.35
EUR606025	600	600	250	2	2	609.00
EUR606030	600	600	300	2	2	622.00
EUR705020	700	500	200	2	2	485.90
EUR705025	700	500	250	2	2	589.10
EUR806020	800	600	200	2	2	649.50
EUR806025	800	600	250	2	2	745.75
EUR808025	800	800	250	4	2	825.55
EUR1006030	1000	600	300	2	2	933.80
EUR1008030	1000	800	300	4	2	1066.50
EUR10010030	1000	1000	300	4	2	1120.35
EUR1208030	1200	800	300	4	2	1262.70
EUR12010030	1200	1000	300	4	2	1294.20

Eureka



EUR403020



2009/10 CATALOGUE

Packed with all the products N.A.W. Controls has been well known for, as well as plenty of new products.

This catalogue showcases the full range of products from our local and overseas suppliers which again will demonstrate that N.A.W. Controls is truly the "ONE STOP SHOP" for your industrial electrical requirements.

For a copy of the catalogue, give N.A.W. Controls a call on (03) 9464 6555, or visit our website.

N.A.W. Controls reserves the right to change specifications, modify pricing and designs without prior notice.

98 Commercial Drive, Thomastown Victoria 3074
Telephone: (03) 9464 6555 Fax: (03) 9464 5155
Email: sales@nawcontrols.com.au
Web: www.nawcontrols.com.au